

EARTH GYPSUM PLASTER BOND



NO HACKING NO WIRE MESH NO DE-BONDING.....GO FOR PLASTER BOND

Plaster Bond is a bonding agent provides excellent performances to bond Gypsum based plaster an RCC background for internal plastering system. It is specially formulated ready to use adhesive consists in organ resins, aggregates and additives to eliminate roughening / hacking and putting wire mesh on Concrete surface. It is an ultimate choice to put a single coat brush / roller application which is comprehensive and safe solution for the Gypsum plasters. Available packing size 1, 5, 10 & 20 Kg. cane.

COMMON ISSUES FACED WHILE SURFACE PREPARATION

Providing mechanical key instead of hacking. Hacking is always problematic for the applicators. Fitting the mash (jail) on the roof.


To solve such kind of problems, an intelligent team of Earth research introduce a strong and reliable bond between the plaster and subtract surface called BONDING AGENT.

Product Features

- * Excellent cohesive bond to RCC, Concrete and other surface.
- * Fine aggregate provides good mechanical bonding.
- * Eliminating hacking / fixing wire mesh for plastering on direct RCC surface.
- * Higher coverage.
- * Ready to use nothing to be added at site .
- * Due to Red colour it is easy to identify the covered area during application.
- * Easy application by Brush / Roller.
- * Plaster application can begin immediate drying the coat.
- * No post/pre-curing is required.

Tips to Use

- * Ensure the substrate is free from dust, wetness and mould oil.
- * Use wider paint brush / roller and clean them before and after application.
- * Stir well before use the adhesive as the aggregates spread uniform.
- * Allow to the coat dry thoroughly (Aprox. 24 hours) before plastering work start.
- * Coated surface should be plastered within 10 days.
- * Recommended Earth Gypsum plasters with this adhesive for RCC surface.
- * Do not add water.



Safety



Bonding



No Disachment



No Hacking



Crack Free

EARTH GYPSUM PLASTER BOND

PRECAUTION

- Do not apply on fire place.
- Do not apply on a wet surface
- Do not apply on the door and window frames.
- Do not apply on decorative surfaces, as once dried it will have to be scrapped or Washed for removing the same.

Technical Specification

Parameter	Earth Gypsum Plaster Bond
Ingredients	Regin + Aggregate
Background	RCC
Coverage (m ² /kg)	6
Colour	Red
Soluble	In Water
Sustainability (°C)	2 - 50



Safety



Bonding



No Detachment



No Hacking



Crack Free